

MODEL
SELECTION

WEIGHT
TRAILERING RATINGS

MOUNTING
HITCH OPTIONS

CARGO
TRAILERING TIPS

2012 GMC TRAILERING GUIDE

WE ARE PROFESSIONAL GRADE

GMC



TRAILERING CAPABILITIES YOU CAN COUNT ON

GMC is about pushing the limits of what's possible for people, like you, who appreciate the details of well-engineered products and who know that things worth doing are worth doing well. Our dedication to innovation through technology leads us to constantly perfect ideas that put more into your vehicle. We build professional-grade vehicles that offer a combination of performance, technology, capability and convenience you might not expect in any single vehicle.

From vehicles like the GMC Sierra HD, our strongest, smartest and most powerful Sierra pickups ever, that offer the best-in-class 1-ton max fifth-wheel trailering capability of 23,000 lbs¹ and best-in-class max payload capacity of 7215 lbs²; to the Sierra 1500 that offers you over 300 horsepower and 22 EPA-estimated highway miles per gallon in the same engine-V-8 fuel economy that no other competitor can beat; to the GMC Terrain, our latest member of the GMC family that provides best-in-class standard highway fuel economy³ and best-in-class maximum second-row leg room. Offering surprising technology features like standard Rear-Vision Camera and available ColorTouch Radio with IntelliLink, they all show how experience and innovation can overcome compromise. That's what happens when our engineers never say never. That's GMC. We Are Professional Grade.

¹When properly equipped. Max trailer weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your GMC dealer for additional details. ²When properly equipped. Max payload capacity includes weight of driver, passengers, optional equipment and cargo. ³EPA-estimated mpg (2WD) 32 hwy. Based on 2011 GM Compact SUV-Crossover segment. Excludes other GM vehicles.

TABLE OF CONTENTS

3	SELECTING A VEHICLE
5	VEHICLES AND HITCHES
7	POWER AND PERFORMANCE
9	TRAILERING TERMS
10	DRIVE TYPES
11	TRAILERING ON THE ROAD
12	DINGHY TOWING CAPABILITY
13	SIERRA TRAILER WEIGHT RATINGS
17	YUKON AND TERRAIN TRAILER WEIGHT RATINGS
19	CANYON, ACADIA AND SAVANA TRAILER WEIGHT RATINGS



TRAILERING GUIDE
SELECTING A VEHICLE


Every GMC truck, crossover, SUV and van is designed specifically for trailering, with power, handling and convenience features you can rely on for long hauls and heavy loads. This guide will help you select the GMC model that's right for your trailering needs, and also contains helpful tips for loading, driving and parking with your trailer.



TRAILERING GUIDE

MAXIMUM TRAILER WEIGHT RATING (LBS)¹

The chart below gives you an idea of the maximum amount of weight you can confidently and safely trailer with different GMC model lines when your vehicle is properly equipped. When determining the total weight of trailer and cargo, include the weight of any additional passengers and optional equipment (driver weight and base equipment are already included). See pages 13-19 for maximum trailer weight ratings by specific model.




¹Maximum trailer weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your GMC dealer for additional details. ²Requires Trailing Package (V92), which includes a factory-installed trailer hitch platform, seven-pin electrical plug and a Heavy-Duty Cooling Package. ³Requires Heavy-Duty Trailing Package (K5L). ⁴Savana 3500 RWD with Duramax Diesel engine (LGH). ⁵Sierra 1500 Extended Cab 2WD with standard box and Max Trailing Package. ⁶Sierra 3500HD Regular Cab 4WD DRW with Duramax Diesel engine (LML).


TRAILERING GUIDE
VEHICLES AND HITCHES



HITCH BALL ON STEP BUMPER




HITCH BALL ON DRAW BAR



WEIGHT-DISTRIBUTING HITCH



FIFTH-WHEEL HITCH



GOOSENECK HITCH

- >> **SELECTING THE RIGHT HITCH** Choosing the right hitch and making the proper electrical connections affects how your vehicle handles, corners and brakes, and allows you to alert other drivers of your intentions. Before selecting a hitch or trailering package, you should be familiar with the weight ratings specific to your GMC vehicle, which are detailed on pages 13-19.
- >> **SELECTING TRAILERING EQUIPMENT** Every GMC vehicle features a variety of standard and available equipment for enhanced trailering performance. Aside from the equipment described below, features such as heavy-duty cooling and extendable trailering mirrors may be available. See your GMC dealer for more information on the model you're interested in.
- >> **WEIGHT-CARRYING HITCH** This consists of a hitch ball mounted to a step bumper or draw bar, commonly used for trailering light and medium loads. Hitch balls are available in a range of sizes. Make sure that the diameter of your hitch ball matches your trailer coupler. Also check that the ball meets or exceeds the gross trailer weight rating¹.
- >> **WEIGHT-DISTRIBUTING HITCH** This is most often used for heavier trailering. This hitch type more evenly distributes the trailer load by using spring bars to shift some of the hitch weight forward onto the tow vehicle's front axle, and rearward to the trailer's axles¹.
- >> **FIFTH-WHEEL HITCH AND GOOSENECK HITCH** These are designed for heavy trailering. Located in the bed of the truck, these hitches position the trailer's kingpin weight over or slightly in front of the truck's rear axle. Fifth-wheel and gooseneck hitches are most frequently used with travel trailers, horse trailers and other large trailers².
- >> **TRAILERING PACKAGE** An optional Heavy-Duty Trailering Equipment Package is available for a wide variety of GMC models (and is standard on some Sierra and Yukon models). The package includes a trailer hitch platform and may include other trailering equipment.
- >> **WIRING HARNESS** This allows you to connect the electrical components of your trailer, such as signal and brake lights, to the trailering vehicle. Select Sierra models and all Yukon models feature a seven-pin wiring harness to streamline hookup of trailer lighting and brakes, and a bussed electrical center makes it easier to connect an electrical trailer brake controller.
- >> **INTEGRATED BRAKE CONTROLLER** This is optional on most Sierra pickups and Yukon models. Completely integrated within the electrical system and its antilock braking system, it allows your trailer's brakes to operate simultaneously with the vehicle's brakes.
- >> **TRAILER BRAKES** These are required above 2000-lb trailer weight on Sierra and Yukon, and above 1000-lb trailer weight on all other models. The most common trailer braking systems are surge brakes (found primarily on boat trailers) and electric brakes (often used on travel trailers, horse trailers and car haulers). Surge brakes are a self-contained hydraulic brake system on the trailer, activated during deceleration as the trailer coupler pushes on the hitch ball. An electric trailer brake system uses a brake control unit mounted inside the trailering vehicle; it operates by sensing the vehicle brakes and then applying the trailer brakes.


TRAILERING GUIDE VEHICLES AND HITCHES

- >> **SERIES** In general, a higher series number indicates a greater load-carrying capacity. In addition, a vehicle with a higher series number typically has a stronger frame, more rigid chassis and higher-capacity brakes, increasing the vehicle's ability to trailer heavy loads.
- >> **OPEN-CARGO, CLOSED-CARGO VEHICLES** There are two types of GMC vehicles: open-cargo (Sierra, Canyon), designed primarily for carrying lots of cargo; and closed-cargo (Acadia, Yukon, Terrain, Savana), for carrying both cargo and passengers. The multipurpose capabilities of our full range of closed-cargo vehicles make them good choices for drivers with broad driving requirements.



TRAILERING GUIDE
POWER AND PERFORMANCE

The engines in GMC vehicles are specifically designed to provide the power and performance needed to handle light, medium or heavy loads over the long haul. They consistently deliver the high torque ratings needed to pull heavy loads and the horsepower needed to keep you moving down the road with confidence and control.



VORTEC 5.3L V-8 VVT (LC9)

VORTEC CYLINDER HEAD

The Vortec engine's unique cylinder head design effectively mixes the intake charge to improve the air/fuel mixture for enhanced performance.

ADVANCED COOLING SYSTEM

The Vortec's cooling system distributes equal amounts of coolant to the cylinder case for more efficient cooling.

BALANCED CRANKSHAFT

An internally balanced crankshaft reduces stress for enhanced durability.

ELECTRONIC THROTTLE CONTROL

An Electronic Throttle Control system optimizes drivability and fuel economy¹ as well as reduces emissions.

- >> **DURAMAX DIESEL V-8 AND ALLISON 6-SPEED AUTOMATIC TRANSMISSION** Sierra Heavy Duty models are available with the Duramax Diesel 6.6L V-8 Turbo engine and the Allison 6-speed automatic transmission. The Allison transmission's target lifespan of up to 200,000 miles² is made possible through the use of larger, heavier components than normally found in 1-ton pickups. With an extraordinary 765 lb-ft of torque, the Duramax Diesel makes the 3500HD the most powerful Sierra HD ever.
- >> **VORTEC ENGINE TECHNOLOGY** Mile after mile, our Vortec engines reassert their reputation for stand-up performance and innovative, breakthrough engineering. This performance all starts with a unique cylinder head design: By developing an effective air flow velocity and path, just as a tornado twists a column of air, the Vortec cylinder head improves the air/fuel mix for better performance and fuel efficiency. In addition, the coil-near-plug ignition produces a reliable spark, and a stiff engine block provides superior vibration damping.
- >> **LOCKING REAR DIFFERENTIAL** Many GMC models are available with an Eaton® automatic locking rear differential, designed to improve low-speed traction of your 2WD or 4WD vehicle. The differential engages when the speed difference between the rear tires reaches approximately 100 rpm. Once the differential engages, both rear wheels rotate at the same speed, providing more of the driveline's torque to the tire with better traction.

¹EPA-estimated city/hwy mpg: Sierra XFE with Vortec 5.3L V-8, 15/22; Yukon with Vortec 5.3L V-8, 15/21; Yukon XL with Vortec 5.3L V-8, 15/21. ²Maintenance needs vary with different driving conditions.

TRAILERING GUIDE

POWER AND PERFORMANCE

For trailering, GMC recommends an automatic transmission for convenience and improved performance. Sierra Heavy Duty trucks equipped with a Duramax engine are available with an Allison 6-speed automatic with Tow/Haul mode, which raises upshift points to use more of the engine's power for strong acceleration and raises downshift points to help slow your truck using engine braking. The 6-speed automatic transmission that comes standard on Yukon, Yukon XL, Yukon Denali and Yukon XL Denali, and is available with Sierra, includes Tow/Haul mode. It includes a passive shift stabilization feature that helps eliminate overactive shifting, a shift schedule to contribute to the solid shift feel, improved transmission life and overall trailering capability.

SELECTED HORSEPOWER AND TORQUE RATINGS

ENGINE HP @ RPM TORQUE LB-FT @ RPM	CANYON	SIERRA 1500	SIERRA DENALI	SIERRA HEAVY DUTY	ACADIA/ ACADIA DENALI	TERRAIN	YUKON	YUKON XL	YUKON DENALI	YUKON XL DENALI	SAVANA
2.4L I-4 VVT DI (LGA)						182 @ 6700 172 @ 4900					
2.9L I-4 VVT (LLV)	185 @ 5600 190 @ 2800										
3.0L V-6 VVT DI (LFW)						264 @ 6950 222 @ 5100					
3.6L V-6 VVT DI (LLT)					288 @ 6300 270 @ 3400						
3.7L I-5 VVT (LLR)	242 @ 5600 242 @ 4600										
4.3L V-6 (LU3)		195 @ 4600 260 @ 2800									
4.8L V-8 (L20)		302 @ 5600 305 @ 4600									280 @ 5200 295 @ 4600
5.3L V-8 (LMG) GAS		315 @ 5200 335 @ 4000					320 @ 5400 335 @ 4000	320 @ 5400 335 @ 4000			
5.3L V-8 (LMG) E85		326 @ 5300 348 @ 4400					326 @ 5300 348 @ 4400	326 @ 5300 348 @ 4400			
5.3L V-8 (LH9)	300 @ 5200 320 @ 3600										
5.3L V-8 (LMF)											310 @ 5200 334 @ 4500
5.3L V-8 (LC9) GAS		315 @ 5200 335 @ 4000					320 @ 5400 335 @ 4000	320 @ 5400 335 @ 4000			
5.3L V-8 (LC9) E85		326 @ 5300 348 @ 4400					326 @ 5300 348 @ 4400	326 @ 5300 348 @ 4400			
6.0L V-8 VVT (L96)				360 @ 5400 ¹ 322 @ 5400 ² 380 @ 4200				352 @ 5400 ³ 382 @ 4200 ³			323 @ 4600 373 @ 4400
6.0L V-8 VVT (LZ1) HYBRID		332 @ 5100 367 @ 4100					332 @ 5100 367 @ 4100		332 @ 5100 367 @ 4100		
6.2L V-8 VVT (L9H)		403 @ 5700 417 @ 4300	403 @ 5700 417 @ 4300								
6.2L V-8 VVT (L94)									403 @ 5700 417 @ 4300	403 @ 5700 417 @ 4300	
6.6L V-8 TURBO DIESEL (LML)				397 @ 3000 765 @ 1600							
6.6L V-8 TURBO DIESEL (LGH)											260 @ 3100 525 @ 1600

¹Horsepower for vehicles less than 10,000 lbs GVWR. ²Horsepower for vehicles greater than 10,000 lbs GVWR. ³Standard and only available on Yukon XL ¾-ton models.

SPECIAL GMC FEATURES

6-SPEED TRANSMISSION Select Yukon, Sierra ½-ton and Heavy Duty models and Savana models offer an electronically controlled 6-speed automatic transmission with overdrive and Tow/Haul mode. Sierra Heavy Duty models with the Duramax Diesel 6.6L V-8 Turbo use an Allison 6-speed transmission with engine grade braking and Tow/Haul mode.

TOW/HAUL MODE An innovative Tow/Haul mode gives automatic transmissions on select models a dual-mode shift program. This feature raises upshift points to use more of the engine's power for strong acceleration and raises downshift points to help slow your truck using engine braking.

RANGE SELECTION MODE To enable this feature, move the column shift lever to the "M" position. The current range will appear next to the "M," indicating the highest attainable range with all lower gears accessible. For instance, when 4th gear is selected, 1st through 4th gears are available. By using the +/- button located on the column shift lever, the driver can select the range of gears desired for the current driving conditions. This feature also allows drivers to control engine and vehicle speed while going downhill by enabling the selection of the preferred range. While using the Range Selection feature, cruise control and Tow/Haul mode are available. This feature is standard on Yukon and Sierra HD and available on select Sierra ½-ton and Savana models.

TRAILER SWAY CONTROL On single-rear-wheel Sierra models and Yukon ½-ton models, this system works with StabiliTrak to minimize trailer sway by applying vehicle and/or trailer brakes. [Excludes Sierra and Yukon Hybrid models.]

"SMART" EXHAUST BRAKING POWER The diesel exhaust brake is an innovative standard feature for Duramax models. Unlike the traditional "on/off" diesel exhaust brakes, the driver-selectable "smart" brake varies negative torque needed based on the truck load and grade. This helps reduce brake fade, extends brake life and gives drivers plenty of confidence when hauling heavy loads downhill.

HILL START BRAKE ASSIST This feature senses potential "rollback" when braking on an incline, and then holds full brake pressure when you lift your foot from the pedal. It gives you an extra 1.5 seconds to apply power and pull away. This peace of mind is standard on select GMC models.

INTEGRATED BRAKE CONTROLLER Select Sierra pickups and Yukon models offer an optional trailer brake controller. It's completely integrated within the vehicle's electrical system and its antilock braking system. It allows your trailer's brakes to operate simultaneously with the vehicle's brakes.

HIGH-QUALITY HEADLAMPS GMC vehicle headlamps are designed to provide the strong low- and high-beam output needed for confident driving at night and during inclement weather conditions.

TRAILERING MIRRORS Heated, manually extendable, power-adjustable mirrors with turn signals in the glass are available for Sierra and Yukon XL ¾-ton.

REAR-VISION CAMERA SYSTEM Make it easier to back up to a trailer or negotiate a tight space. This available system places a monitor in your rearview mirror (or navigation screen, if equipped) to display a view of the area behind the vehicle. The Rear-Vision Camera System does not replace driver vision. Please use proper care when backing up.

GROSS AXLE WEIGHT RATING (GAWR) This is the weight in pounds each axle is capable of supporting. The load on each axle must not exceed its GAWR. The GAWR for each GMC vehicle is displayed on the driver's door or door-lock pillar label.

GROSS COMBINATION WEIGHT RATING (GCWR) This is the maximum allowable weight, expressed in pounds, of the vehicle and trailer combination, including the weight of the driver, passengers, fuel, optional equipment and gear in the vehicle.

GROSS TRAILER WEIGHT The weight of a loaded trailer.

TRAILER WEIGHT RATING The trailer weight rating for any vehicle is determined by subtracting vehicle weight from GCWR. At the trailer weight rating for a properly equipped vehicle, you should be able to accelerate and merge with traffic, climb typical interstate grades at highway speeds, have control on varying road surfaces and stop adequately within a reasonable distance.

GROSS VEHICLE WEIGHT RATING (GVWR) This number, in pounds, is the maximum amount a tow vehicle may weigh. Everything that contributes to the weight of the tow vehicle is featured in this rating, including the weight of the vehicle, driver and all passengers, fuel, payload, tongue load of the trailer, weight of hitch and all optional equipment. The GVWR is displayed on the driver's door or door-lock pillar label of your GMC vehicle.

TONGUE (OR HITCH) WEIGHT The tongue weight is the total amount of trailer weight that is pressing down on the trailer hitch. Keep in mind that the way a trailer is loaded affects the overall tongue weight and will also affect the handling of the tow vehicle when trailering.

HEADLAMP



EASY TAPSHIFTING



TRAILERING MIRRORS



TRAILERING GUIDE
DRIVE TYPES

ALL-WHEEL DRIVE (AWD) This is great if you'll be trailering over wet or snow-covered roads on a regular basis. The Yukon Denali and Yukon XL Denali, Sierra Denali, Acadia, Acadia Denali, Terrain and selected Savana models offer available advanced AWD designs that distribute power to front and rear axles, allowing every wheel to provide driving power.

REAR-WHEEL DRIVE Rear-wheel-drive models are available on Sierra, Sierra HD, Yukon, Yukon Denali, Canyon and Savana vehicles. The addition of cargo increases weight on the rear, increasing traction. Rear-wheel-drive vehicles typically have lighter chassis weights, resulting in better fuel economy¹ than all-wheel-drive and four-wheel-drive vehicles. The lighter chassis also allows you to dedicate more of the vehicle's load-carrying capacity to cargo weight².

FOUR-WHEEL DRIVE This gives you the option of enjoying outstanding traction on demand. Yukon, Yukon XL and Sierra are available with AutoTrac (Insta-Trac is standard on Canyon) – our automatic four-wheel-drive system. When set in Auto 4WD mode, AutoTrac detects wheel slippage and automatically transfers torque to the front wheels. When conditions warrant, the system automatically returns to two-wheel drive.

TRAILER CLASSIFICATION	TYPICAL EXAMPLES	WEIGHT RANGE	TYPICAL HITCH TYPE ³	TYPICAL HITCH (TONGUE) WEIGHT
LIGHT-DUTY (I)	Folding camping trailer, snowmobiles and jet-ski trailers (trailer and cargo combined)	Up to 2000 lbs gross trailer weight	Weight-carrying hitch	10%-15% of gross trailer weight (200 lbs maximum)
MEDIUM-DUTY (II)	Single-axle trailers up to 18 ft., open utility trailers and small speedboats	2001-3500 lbs gross trailer weight	Weight-carrying hitch	10%-15% of gross trailer weight (350 lbs maximum)
HEAVY-DUTY (III)	Dual- or single-axle trailers, larger boats and enclosed utility trailers	3501-5000 lbs gross trailer weight	Weight-carrying hitch or weight-distributing hitch	10%-15% of gross trailer weight (500 lbs maximum)
EXTRA HEAVY-DUTY (IV)	Two-horse, travel and fifth-wheel recreational trailers	5001-10,000 lbs gross trailer weight	Weight-distributing hitch or fifth-wheel hitch	10%-15% of gross trailer weight (1200 lbs maximum)
MAXIMUM HEAVY-DUTY (V)	Largest horse, travel and fifth-wheel recreational or commercial trailers	10,001 lbs and above gross trailer weight	Weight-distributing hitch, fifth-wheel or gooseneck hitch	10%-15% of gross trailer weight (1500 lbs maximum for weight-distributing hitch) 15%-25% of gross trailer weight (3500 lbs maximum for fifth-wheel or gooseneck hitch)

¹EPA-estimated mpg: Canyon Crew Cab 2WD with 2.9L I-4 engine, 18 city/25 hwy.; Savana 1500 2WD with 5.3L V-8 engine, 13 city/17 hwy.; Sierra 1500 XFE with 5.3L V-8 engine, 15 city/22 hwy.; Yukon with 5.3L V-8 engine, 15 city/21 hwy. ²Cargo and load capacity limited by weight and distribution. ³Represents minimum recommended hitches. Please refer to your trailer's Owner's Manual or ask your GMC sales professional.

BEFORE YOU TRAILER

- >> **SAFETY CHAINS** Always attach safety chains between your vehicle and your trailer and cross them under the tongue of the trailer so that the tongue will be less likely to drop if the trailer should separate from the hitch. Leave enough slack in the chains so you can corner without the chains impeding the movement of the trailer. Do not allow safety chains to drag on the ground.
- >> **LOADING YOUR TRAILER** Load your trailer to attain a 10-15 percent tongue weight. A good rule of thumb is to distribute 60 percent of the load over the front half of the trailer and evenly from side to side. Loads sitting either too far forward or too far back in the trailer can create unstable trailering conditions – such as trailer sway – at highway speeds and during heavy braking. Once the trailer has been loaded and the weight is distributed properly, all cargo should be secured to prevent the load from shifting.
- >> **SAFETY CHECKLIST** Before starting out on a trip, double-check the hitch and platform, the hitch nuts and bolts, mirror adjustments, safety chains and vehicle and trailer lights. Make sure that a sway-control device is installed, if required, and that the device is working properly [see charts on pages 13-19]. Check tire pressure on both the tow vehicle and the trailer. If your trailer has electric brakes, test them by manually engaging the brake controller while the vehicle is moving slowly. Check to see that the breakaway switch, if available, is connected and functioning properly. Finally, make certain that all loads are secure.

ON THE ROAD

- >> **ACCELERATING / BRAKING** Avoid overworking your engine when trailering by applying gradual pressure on the accelerator. Allow your vehicle to safely reach a comfortable driving speed. Give yourself extra time and room when merging onto highways. Braking when pulling a trailer requires extra distance. Allow ample room to come to a safe stop. A good measure for determining a safe following distance is to allow one vehicle and trailer length between you and the vehicle ahead for every 10 mph of speed. When braking, use firm, steady pressure on the brake pedal.
- >> **CONTROLLING TRAILER SWAY** Sway refers to instability of the trailer relative to the trailer vehicle, and often results from improper weight distribution, excessive speed or overloading. Other factors can cause sway: crosswinds, poor vehicle maintenance and road conditions. Trying to steer out of sway will likely make it worse. Speed is a major contributor to trailer sway, so you need to slow the vehicle – braking, however, could lead to a jackknife or other loss of control. To control sway:
 - Hold the steering wheel as steady as possible.
 - Release the accelerator but do not touch the brake pedal.
 - Activate electric trailer brakes (if equipped) by hand, until the sway condition stops.
 - Use the vehicle brakes to come to a complete stop.

You should then pull your vehicle to the side of the road and attempt to determine the cause of the instability. Check the cargo load for shifting and improper weight distribution. Check tire pressure on the tow vehicle and trailer, and the condition of the suspension and shocks. If the sway was caused by strong winds, wait for conditions to improve before continuing your trip. Finally, some trailers can be equipped with anti-sway devices. Contact the manufacturer of your trailer for availability.

TRAILERING GUIDE
DINGHY TOWING CAPABILITY

- >> **CORNERING** The turning radius of a trailer is typically much smaller than that of your vehicle; therefore, a trailer may hit soft shoulders, curbs, trees or other objects when making tight turns. Taking turns sharply can also cause the trailer to strike against and damage the tow vehicle. When approaching a sharp corner, brake sooner than normal to reduce vehicle speed before entering the turn. Drive the vehicle slightly past the normal turning point and then firmly turn the steering wheel. By cornering at a wider angle, both vehicle and trailer should safely clear the inside of the turn.
- >> **PASSING** When passing, allow additional time and distance to safely pass the other vehicle. Signal your intention to pass well in advance and, when reentering the lane, make certain your trailer is clear of the vehicle you have passed. Never pass on hills or around curves.
- >> **BACKING UP** To back up a trailer, place one hand at the 6 o'clock position on the steering wheel. To move the trailer to the left, move your hand to the left. To move the trailer to the right, move your hand to the right. Back up slowly, and move the steering wheel in small increments to help maintain control. To assist in backing up, it is helpful to have someone outside the vehicle to guide you. Make certain you can see your spotter at all times.
- >> **DRIVING ON GRADES** Before going down a steep incline, reduce your speed and shift the transmission into a lower gear. This provides "engine braking" and reduces the need to brake for long periods. When driving up a steep grade, shift to a lower gear for more torque to maintain speed and avoid lugging. Lugging occurs when the vehicle's engine stutters because it needs to be in a lower gear. Crest the hill no faster than the speed at which you want to descend and in the gear you expect will require little braking. Pay attention to your temperature gauges for any signs of overheating.

- >> **OVERHEATING** Prolonged driving with overheated fluids can cause damage to your vehicle. If temperature gauges register abnormally high, if there is a marked decrease in power or if you hear unusual engine noises, immediately take the following steps:
 - Pull your vehicle to the side of the road. Once stopped, shift into park (automatic transmissions) or neutral (manual transmissions) and apply the parking brakes. Leave the engine running.
 - Turn off air conditioning and other accessories to reduce load on the engine. Roll down the windows and turn the heater on to maximum and the fan to its highest setting. The heater core provides a second cooling surface that can help reduce engine temperatures.
 - If you suspect that the overheating is the result of climbing a long, steep grade, run the engine at fast idle (around 1500 rpm) until the temperature gauge registers a normal reading.
 - With the vehicle in park or neutral and the parking brake engaged and being mindful of traffic, exit your vehicle and look for steam or leaking coolant underneath the engine. If you see either of these, shut the engine off and allow the engine to cool. To avoid being burned, do not attempt to remove the radiator cap until the engine has cooled.
- >> **PARKING ON GRADES** Parking on steep grades with a trailer is not recommended; if you must, follow this procedure:
 - Apply the brakes and shift into neutral.
 - Have someone block the trailer's wheels on the downgrade side.
 - Release the brakes until the blocks absorb the load.
 - Apply the parking brake and shift into park.
- >> **LEAVING YOUR PARKING SPOT ON GRADES**
 - Hold the brake pedal down and start the engine.
 - Shift into gear and release the parking brake.
 - Release brake and drive uphill slightly until free from the blocks.
 - Apply brakes and have someone retrieve the blocks.

FLAT (DINGHY) TOWING CAPABILITY	ACADIA/ ACADIA DENALI	CANYON	TERRAIN	SAVANA	SIERRA	YUKON	YUKON XL	YUKON DENALI/ XL DENALI
2WD	YES	NO	YES	NO	NO	NO	NO	NO
4WD	-	YES	-	-	YES	YES ¹	YES ¹	-
AWD	YES	-	YES	NO	NO	-	-	NO

¹Requires 2-speed transfer case.

TRAILERING GUIDE

SIERRA TRAILER WEIGHT RATINGS

These charts specify the maximum trailer weight for your vehicle, assuming use of a weight-distributing hitch. (For fifth-wheel or gooseneck ratings, see page 14.) The maximum rating for a weight-carrying hitch is listed below the charts. Do not exceed the maximum trailer weight rating. When properly equipped, maximum trailer weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your GMC dealer for additional details. Some models, when loaded with the driver, passenger and maximum tongue load, may exceed the maximum Gross Vehicle Weight Rating (GVWR) or rear-axle weight rating for that vehicle, which is not permissible. For more information, ask your GMC sales professional or call 1-800-GMC-8782.

SIERRA 1500 AUTOMATIC TRANSMISSION RATINGS WITH BALL HITCH

	VORTEC 4.3L V-6		VORTEC 4.8L V-8 FLEXFUEL		VORTEC 5.3L V-8 FLEXFUEL		VORTEC 6.0L V-8 HYBRID		VORTEC 6.2L V-8	
	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY
REG CAB STANDARD BOX 2WD	3.23 3.73	4800 5400	3.23 3.73	4700 7200	3.08 3.42	7400 9100				
REG CAB STANDARD BOX 4WD	3.73	5100	3.42	6000	3.08 3.42	7100 8900				
REG CAB LONG BOX 2WD	3.23 3.73	4700 5200	3.23 3.73	5100 7100	3.08 3.42	7200 10,000				
REG CAB LONG BOX 4WD	3.73	4900	3.42	5800	3.08 3.42	7000 9800				
EXT. CAB STANDARD BOX 2WD	3.23	4400	3.23 3.73	4700 6700	3.08 3.42	6900 9700			3.42	9700
EXT. CAB STANDARD BOX 2WD WITH MAX TRAILERING PACKAGE									3.73	10,700
EXT. CAB STANDARD BOX 4WD			3.42	5500	3.08 3.42	6800 9600			3.42	9400
EXT. CAB STANDARD BOX 4WD WITH MAX TRAILERING PACKAGE									3.73	10,400
EXT. CAB LONG BOX 2WD					3.08 3.42	6700 9500				
EXT. CAB LONG BOX 4WD					3.08 3.42	6500 9300				
CREW CAB SHORT BOX 2WD			3.23 3.73	4700 6700	3.08 3.42	6900 9600	3.08	6100	3.42	9700
CREW CAB SHORT BOX 2WD XFE					3.08	7000				
CREW CAB SHORT BOX 2WD WITH MAX TRAILERING PACKAGE									3.73	10,600
CREW CAB SHORT BOX 4WD			3.42	5500	3.08 3.42	6700 9500	3.08	5900	3.42	9400
CREW CAB SHORT BOX 4WD WITH MAX TRAILERING PACKAGE									3.73	10,400
SIERRA DENALI CREW CAB SHORT BOX 2WD									3.42	9600
SIERRA DENALI CREW CAB SHORT BOX 4WD									3.42	9400

*Maximum trailer weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your GMC dealer for additional details.

These charts are for use with a weight-distributing hitch. When using a weight-carrying hitch, the maximum trailer weight is 5000 lbs and a 600-lb trailer tongue weight. A weight-distributing hitch-and-sway control is required for trailer weights greater than 5000 lbs.

GENERAL TRAILERING NOTES: A seven-wire trailering harness is standard on 1500 Series models. Where available, the Heavy-Duty Trailering Equipment Package (Z82) provides a trailer hitch platform and a seven-pin sealed connector at the rear bumper. **WEIGHT-DISTRIBUTING HITCH NOTES:** Trailer tongue weight should be 10 percent to 15 percent of total loaded trailer weight. For 1500 Series models, trailer tongue weight should be up to 1100 lbs. The addition of trailer tongue weight must not cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). **1500 SERIES MODEL NOTES:** For automatic transmission models, an additional transmission oil cooler (KNP) is available.

TRAILERING GUIDE
SIERRA TRAILER WEIGHT RATINGS

GMC TRAILER WEIGHT RATINGS (CONTINUED)

SIERRA 1500 AUTOMATIC TRANSMISSION RATINGS WITH GOOSENECK/FIFTH-WHEEL TRAILER	VORTEC 4.3L V-6		VORTEC 4.8L V-8 FLEXFUEL		VORTEC 5.3L V-8 FLEXFUEL		VORTEC 6.0L V-8 HYBRID		VORTEC 6.2L V-8	
	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY
REG CAB STANDARD BOX 2WD					3.42	9200				
REG CAB STANDARD BOX 4WD					3.42	8200				
REG CAB LONG BOX 2WD					3.42	8900				
REG CAB LONG BOX 4WD					3.42	9700				
EXT. CAB STANDARD BOX 2WD					3.42	9400			3.42	9400
EXT. CAB STANDARD BOX 2WD WITH MAX TRAILERING PACKAGE									3.73	10,600
EXT. CAB STANDARD BOX 4WD					3.42	9600			3.42	9100
EXT. CAB STANDARD BOX 4WD WITH MAX TRAILERING PACKAGE									3.73	10,300
EXT. CAB LONG BOX 2WD					3.42	9000				
EXT. CAB LONG BOX 4WD					3.42	8100				
CREW CAB SHORT BOX 2WD										
CREW CAB SHORT BOX 4WD										
CREW CAB SHORT BOX 2WD WITH MAX TRAILERING PACKAGE										
CREW CAB SHORT BOX 4WD										
CREW CAB SHORT BOX 4WD WITH MAX TRAILERING PACKAGE										

This chart is for use with fifth-wheel or gooseneck hitches. Automatic transmission ratings with Vortec 6000 engine.

GENERAL TRAILERING NOTES: A seven-wire trailering harness is standard on 1500 Series models. Where available, the Heavy-Duty Trailering Equipment Package (ZB2) provides a trailer hitch platform and a seven-pin sealed connector at the rear bumper. An eight-wire camper/fifth-wheel wiring harness (UY2) is also available and requires the Heavy-Duty Trailering Equipment Package (ZB2).
FIFTH-WHEEL AND GOOSENECK HITCH NOTES: Trailer kingpin weight should be 15 percent to 25 percent of total loaded trailer weight. For 1500 Series models, the trailer kingpin weight should be up to 1500 lbs. The addition of trailer kingpin weight cannot cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). **1500 SERIES MODEL NOTES:** For automatic transmission models, an additional transmission oil cooler (KNP) is available.

TRAILERING GUIDE
SIERRA TRAILER WEIGHT RATINGS

GMC TRAILER WEIGHT RATINGS (CONTINUED)

SIERRA HD AUTOMATIC TRANSMISSION RATINGS WITH BALL HITCH ¹	VORTEC 6.0L V-8		DURAMAX 6.6L V-8 DIESEL		SIERRA HD AUTOMATIC TRANSMISSION RATINGS WITH GOOSENECK/ FIFTH-WHEEL TRAILER ¹	VORTEC 6.0L V-8		DURAMAX 6.6L V-8 DIESEL	
	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY		AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY
2500HD SERIES REGULAR CAB LONG BOX 2WD ²	3.73 4.10	10,200 13,000	3.73	13,000	2500HD SERIES REGULAR CAB LONG BOX 2WD ²	3.73 4.10	10,200 14,700	3.73	17,800
2500HD SERIES REGULAR CAB LONG BOX 4WD ²	3.73 4.10	9900 13,000	3.73	13,000	2500HD SERIES REGULAR CAB LONG BOX 4WD ²	3.73 4.10	9900 14,400	3.73	17,500
2500HD SERIES EXTENDED CAB STANDARD BOX 2WD ²	3.73 4.10	9800 13,000	3.73	13,000	2500HD SERIES EXTENDED CAB STANDARD BOX 2WD ²	3.73 4.10	9800 14,300	3.73	17,500
2500HD SERIES CREW CAB STANDARD BOX 2WD ²	3.73 4.10	9700 13,000	3.73	13,000	2500HD SERIES CREW CAB STANDARD BOX 2WD ²	3.73 4.10	9700 14,200	3.73	17,400
2500 DENALI HD STANDARD BOX 2WD	3.73 4.10	9500 13,000	3.73	13,000	2500 DENALI HD STANDARD BOX 2WD	3.73 4.10	9500 14,000	3.73	16,500
2500 DENALI HD STANDARD BOX 4WD	3.73 4.10	9300 13,000	3.73	13,000	2500 DENALI HD STANDARD BOX 4WD	3.73 4.10	9300 13,700	3.73	14,700
2500HD SERIES EXTENDED CAB LONG BOX 2WD ²	3.73 4.10	9700 13,000	3.73	13,000	2500HD SERIES EXTENDED CAB LONG BOX 2WD ²	3.73 4.10	9700 14,200	3.73	17,400
2500HD SERIES CREW CAB LONG BOX 2WD	3.73 4.10	9600 13,000	3.73	13,000	2500HD SERIES CREW CAB LONG BOX 2WD	3.73 4.10	9600 14,100	3.73	16,700
2500HD SERIES EXTENDED CAB STANDARD BOX 4WD ²	3.73 4.10	9500 13,000	3.73	13,000	2500HD SERIES EXTENDED CAB STANDARD BOX 4WD ²	3.73 4.10	9500 14,000	3.73	16,400
2500HD SERIES CREW CAB STANDARD BOX 4WD ²	3.73 4.10	9400 13,000	3.73	13,000	2500HD SERIES CREW CAB STANDARD BOX 4WD ²	3.73 4.10	9400 13,900	3.73	15,800
2500HD SERIES EXTENDED CAB LONG BOX 4WD ²	3.73 4.10	9400 13,000	3.73	13,000	2500HD SERIES EXTENDED CAB LONG BOX 4WD ²	3.73 4.10	9400 13,900	3.73	15,700
2500HD SERIES CREW CAB LONG BOX 4WD ²	3.73 4.10	9300 13,000	3.73	13,000	2500HD SERIES CREW CAB LONG BOX 4WD ²	3.73 4.10	9300 13,800	3.73	14,700
3500HD SERIES REGULAR CAB LONG BOX SRW 2WD	4.10	13,000			3500HD SERIES REGULAR CAB LONG BOX SRW 2WD	4.10	14,500		
3500HD SERIES REGULAR CAB LONG BOX DRW 2WD	3.73 4.10	9600 14,100			3500HD SERIES REGULAR CAB LONG BOX DRW 2WD	3.73 4.10	9600 14,100		
3500HD SERIES EXTENDED CAB LONG BOX SRW 2WD ³	3.73 4.10	9500 13,000	3.73	13,000	3500HD SERIES EXTENDED CAB LONG BOX SRW 2WD ³	3.73 4.10	9500 14,000	3.73	17,300
3500HD SERIES EXTENDED CAB LONG BOX DRW 2WD ³	3.73 4.10	9100 13,600	3.73	16,500	3500HD SERIES EXTENDED CAB LONG BOX DRW 2WD ³	3.73 4.10	9100 13,600	3.73	22,800
3500HD SERIES CREW CAB STANDARD BOX SRW 2WD	3.73 4.10	9500 13,000	3.73	13,000	3500HD SERIES CREW CAB STANDARD BOX SRW 2WD	3.73 4.10	9500 14,000	3.73	17,200
3500 DENALI HD CREW CAB STANDARD BOX SRW 2WD	3.73 4.10	9300 13,000	3.73	13,000	3500 DENALI HD CREW CAB STANDARD BOX SRW 2WD	3.73 4.10	9300 13,800	3.73	17,100
3500HD SERIES CREW CAB LONG BOX SRW 2WD ³	3.73 4.10	9400 13,000	3.73	13,000	3500HD SERIES CREW CAB LONG BOX SRW 2WD ³	3.73 4.10	9400 13,900	3.73	17,300

¹Trailer rating limited to 13,000 lbs with weight-carrying or weight-distributing hitch (conventional). ²Fifth-wheel or gooseneck kingpin weight 15 percent to 25 percent of trailer weight up to 3000 lbs (1361 kg) maximum. ³Fifth-wheel or gooseneck kingpin weight 15 percent to 25 percent of trailer weight up to 3500 lbs (1587 kg) maximum.

GENERAL TRAILERING NOTES: A seven-wire trailering harness is standard on Sierra Heavy-Duty models. Where available, the Heavy-Duty Trailering Equipment Package (Z82) provides a trailer hitch platform and a seven-pin sealed connector at the rear bumper. An eight-wire camper/fifth-wheel wiring harness (UY2) is also available and requires the Heavy-Duty Trailering Equipment Package (Z82). **AUTOMATIC TRANSMISSION MODEL NOTE:** All automatic transmission models are equipped with an engine oil cooler (KC4) and an oil-to-air transmission oil cooler (KNP).

TRAILERING GUIDE
SIERRA TRAILER WEIGHT RATINGS

GMC TRAILER WEIGHT RATINGS (CONTINUED)

SIERRA HD AUTOMATIC TRANSMISSION RATINGS WITH BALL HITCH ¹	VORTEC 6.0L V-8		DURAMAX 6.6L V-8 DIESEL		SIERRA HD AUTOMATIC TRANSMISSION RATINGS WITH GOOSENECK/ FIFTH-WHEEL TRAILER ¹	VORTEC 6.0L V-8		DURAMAX 6.6L V-8 DIESEL	
	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY		AXLE RATIO	MAX TRAILER/ TOWING CAPACITY	AXLE RATIO	MAX TRAILER/ TOWING CAPACITY
3500HD SERIES CREW CAB LONG BOX DRW 2WD ²	3.73 4.10	9000 13,500	3.73	16,500	3500HD SERIES CREW CAB LONG BOX DRW 2WD ²	3.73 4.10	9000 13,500	3.73	22,800
3500 DENALI HD CREW CAB LONG BOX DRW 2WD ²	3.73 4.10	8900 13,400	3.73	16,500	3500 DENALI HD CREW CAB LONG BOX DRW 2WD ²	3.73 4.10	8900 13,400	3.73	22,600
3500HD SERIES REGULAR CAB LONG BOX SRW 4WD ²	3.73 4.10	9700 13,000	3.73	13,000	3500HD SERIES REGULAR CAB LONG BOX SRW 4WD ²	3.73 4.10	9700 14,200	3.73	17,400
3500HD SERIES REGULAR CAB LONG BOX DRW 4WD ²	3.73 4.10	9300 13,800	3.73	16,000	3500HD SERIES REGULAR CAB LONG BOX DRW 4WD ²	3.73 4.10	9300 13,800	3.73	23,000
3500HD SERIES EXTENDED CAB LONG BOX SRW 4WD ²	3.73 4.10	9200 13,000	3.73	13,000	3500HD SERIES EXTENDED CAB LONG BOX SRW 4WD ²	3.73 4.10	9200 13,700	3.73	16,900
3500HD SERIES EXTENDED CAB LONG BOX DRW 4WD ²	3.73 4.10	8900 13,400	3.73	18,000	3500HD SERIES EXTENDED CAB LONG BOX DRW 4WD ²	3.73 4.10	8900 13,400	3.73	22,600
3500HD SERIES CREW CAB STANDARD BOX SRW 4WD ²	3.73 4.10	9200 13,000	3.73	13,000	3500HD SERIES CREW CAB STANDARD BOX SRW 4WD ²	3.73 4.10	9200 13,700	3.73	17,000
3500 DENALI HD CREW CAB STANDARD BOX SRW 4WD ²	3.73 4.10	9100 13,000	3.73	13,000	3500 DENALI HD CREW CAB STANDARD BOX SRW 4WD ²	3.73 4.10	9100 13,600	3.73	16,800
3500HD SERIES CREW CAB LONG BOX DRW 4WD ²	3.73 4.10	8700 13,200	3.73	18,000	3500HD SERIES CREW CAB LONG BOX DRW 4WD ²	3.73 4.10	8700 13,200	3.73	22,400
3500 DENALI HD CREW CAB LONG BOX DRW 4WD ²	3.73 4.10	8500 13,000	3.73	18,000	3500 DENALI HD CREW CAB LONG BOX DRW 4WD ²	3.73 4.10	8500 13,000	3.73	22,300

¹Trailer rating limited to 13,000 lbs with weight distributing hitch (conventional). ²Fifth-wheel or gooseneck kingpin weight 15 percent to 25 percent of trailer weight up to 3500 lbs (1587 kg) maximum.

GENERAL TRAILERING NOTES: A seven-wire trailering harness is standard on Sierra Heavy Duty models. Where available, the Heavy-Duty Trailering Equipment Package (Z82) provides a trailer hitch platform and a seven-pin sealed connector at the rear bumper. An eight-wire camper/fifth-wheel wiring harness (UY2) is also available and requires the Heavy-Duty Trailering Equipment Package (Z82). **AUTOMATIC TRANSMISSION MODEL NOTE:** All automatic transmission models are equipped with an engine oil cooler (KC4) and an oil-to-air transmission oil cooler (KNP). **FIFTH-WHEEL AND GOOSENECK HITCH NOTES:** Trailer kingpin weight should be 15 percent to 25 percent of total loaded trailer, up to 2500 lbs on single-rear-wheel (RD4) models or up to 3500 lbs on dual-rear-wheel (RD5) models. The addition of trailer kingpin weight cannot cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).

TRAILERING GUIDE
YUKON AND TERRAIN TRAILER WEIGHT RATINGS

GMC TRAILER WEIGHT RATINGS (CONTINUED)

YUKON YUKON XL YUKON HYBRID YUKON DENALI YUKON XL DENALI YUKON DENALI HYBRID	VORTEC 5.3L V-8		VORTEC 6.0L V-8 VVT		VORTEC 6.0L V-8 HYBRID		VORTEC 6.2L V-8	
	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY
YUKON 1500 2WD	3.08 3.42	5500 8500 ¹			3.08	6200		
YUKON 1500 4WD	3.08 3.42	5200 8200 ¹			3.08	5900		
YUKON XL 1500 2WD	3.08 3.42	5100 8100 ¹						
YUKON XL 1500 4WD	3.08 3.42	5000 8000 ¹						
YUKON XL 2500 2WD			3.73	9600				
YUKON XL 2500 4WD			3.73	9400				
YUKON DENALI 2WD					3.08	6000	3.42	8300
YUKON DENALI AWD					3.08	5700	3.42	8100
YUKON XL DENALI 2WD							3.42	7900
YUKON XL DENALI AWD							3.42	7800

¹Requires Heavy-Duty Cooling Package (K5L).

NOTES ON YUKON, YUKON XL AND YUKON DENALI: Trailer tongue weight should be 10 percent to 15 percent of total loaded trailer weight (up to 1000 lbs). Addition of trailer tongue weight must not cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). The Heavy-Duty Trailering Equipment Package (Z82) includes trailer hitch platform and trailer electrical connector. With 2WD models, Z82 also includes traction control (NW7), air cleaner (K47) and locking differential (G8D).

TERRAIN	VORTEC 2.4L I-4		VORTEC 3.0L V-6 DI	
	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY
TERRAIN FWD	3.23	1500	2.77	3500
TERRAIN AWD	3.53	1500	2.77 3.39	3500 3500

Weight-distributing hitch and sway control not required.

NOTES ON TERRAIN: Trailer tongue weight should be 10 percent to 15 percent of total loaded trailer weight (up to 350 lbs). Addition of trailer tongue weight cannot cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).



CANYON, ACADIA AND SAVANA TRAILER WEIGHT RATINGS

CANYON
AUTOMATIC AND MANUAL
TRANSMISSION RATING WITH
BALL HITCH

	VORTEC 2.9L I-4 VVT		VORTEC 3.7L I-5 VVT		VORTEC 5.3L V-8	
	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY
REGULAR CAB 2WD AUTO	3.73	3400	3.73	4000		
REGULAR CAB 4WD AUTO	3.73	3100	3.73	4000		
EXTENDED CAB 2WD AUTO	3.73	3200	3.73	5500	3.42 3.73	6000 6000
EXTENDED CAB 4WD AUTO	3.73	2900	3.73	5500	3.42 4.10	6000 6000
CREW CAB 2WD AUTO	3.73	3000	3.73	5500	3.42 3.73	6000 6000
CREW CAB 4WD AUTO			3.73	5500	3.42 4.10	6000 6000
REGULAR CAB 2WD MANUAL	3.73	2400				
REGULAR CAB 4WD MANUAL	3.73	2100				
EXTENDED CAB 2WD MANUAL	3.73	2200				
EXTENDED CAB 4WD MANUAL	3.73	1900				

This chart is for use with a weight-distributing hitch. When using a weight-carrying hitch, the maximum trailer weight is 5000 lbs with a 500-lb tongue weight. A weight-distributing hitch-and-sway control is required for trailer weights greater than 5000 lbs.

NOTES ON CANYON: Trailer tongue weight should be 10 percent to 15 percent of total loaded trailer weight (up to 750 lbs). Addition of trailer tongue weight cannot cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). The standard base cooling system includes all content required to attain maximum trailer rating. No optional cooling equipment available.

**ACADIA/
ACADIA DENALI**

	GM 3.6L V-6 VVT DI	
	AXLE RATIO	MAX TRAILER/TOWING CAPACITY
2WD	3.16	5200
AWD	3.16	5200

Weight-distributing hitch-and-sway control not required.

NOTES ON ACADIA: Trailer tongue weight should be 10 percent to 15 percent of total loaded trailer weight (up to 600 lbs). Addition of trailer tongue weight must not cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). The standard base cooling system includes all content required to attain maximum trailer rating. No optional cooling equipment available.

SAVANA

	VORTEC 4.8L V-8		VORTEC 5.3L V-8		VORTEC 6.0L V-8		DURAMAX 6.6L V-8	
	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY	AXLE RATIO	MAX TRAILER/TOWING CAPACITY
1500 2WD/AWD			3.42 3.73	6200/6000 6200/6000				
2500	3.42	6700			3.42	9800		
3500 (135WB/155WB)					3.42	9700/9300	3.54	9900/9700

This chart is for use with a weight-distributing hitch. When using a weight-carrying hitch, the maximum trailer weight is 4000 lbs with a 400-lb tongue weight. A weight-distributing hitch-and-sway control is required for trailer weights greater than 4000 lbs.

NOTES ON SAVANA: Trailer tongue weight should be 10 percent to 15 percent of total loaded trailer weight (up to 1000 lbs). Addition of trailer tongue weight cannot cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). The standard base cooling system includes all content required to attain maximum trailer rating. No optional cooling equipment available. The Heavy-Duty Trailering Equipment Package (Z82) includes trailer hitch platform and seven-wire trailer wiring harness.



TRAILERING WITH YOUR GMC: GMC vehicles are built strong and durable to handle the demands of trailering. Certain equipment that prepares a GMC vehicle for trailering is standard: a large fuel tank, a high-capacity alternator and a front stabilizer bar. For other available trailering-related equipment, talk to your dealer. You'll need a hitch, of course, and a wide selection of hitch types is available, either as factory equipment or from your dealer. In addition, if you plan to tow frequently, you should equip your GMC vehicle with the available Trailering Package. This package includes a weight-distributing hitch platform and an electrical harness. Also required with this package are a hitch ball, a mounting head and weight-distributing and anti-sway assemblies; these are available through aftermarket sources. Please carefully review your GMC Owner's Manual for important safety information about trailering with your vehicle.

A WORD ABOUT THIS GUIDE: We have tried to make this guide comprehensive and factual. We reserve the right, however, to make changes at any time and without notice, in prices, colors, materials, equipment, specifications, models and availability. Information may have been updated since the time of publication. Please check with your GMC sales professional for complete details. GMC reserves the right to lengthen or shorten the model year for any product for any reason, or to start and end model years at different times. GMC vehicles are equipped with engines produced by different operating units of General Motors, its subsidiaries or suppliers to General Motors worldwide. ©2012 General Motors. All rights reserved. GM, the GM logo, GMC, and the slogans, emblems, vehicle model names, vehicle body designs and other marks appearing in this guide are the trademarks and/or service marks of General Motors, its subsidiaries, affiliates and licensors. Eaton is a trademark of Eaton Corporation.